

BR100 Router

Branch Router with built-in 802.11n

The Aerohive Networks BR100 Router marries 802.11n performance, enterprise security and advanced wired/wireless management with cloud computing to deliver a zero-touch branch network deployment.



The **Aerohive Networks BR100** router marries 802.11n performance, enterprise security, and advanced wired/wireless management with cloud computing to deliver a zero-touch branch network deployment.

“Work anywhere” mobility meets enterprise routing and security in a compact device. With HiveOS Routing at its core, the BR100 includes fast roaming, user-based access control, and fully stateful firewall policies, as well as additional security and RF networking features at no extra cost; all without the need for a centralized or dedicated controller. Combining these award-winning capabilities with cloud-based services allows the BR100 to meet your budgetary requirements and blow past your remote workers’ expectations.

Key Features and Benefits

Layer 3 IPsec VPN and Flow-based Stateful Firewall

By using device-based IPsec VPN, HiveOS Routing features running on every BR100 allows remote users to access corporate resources via authenticated devices without the hassle of installing, configuring or maintaining additional VPN software. In addition, an advanced flow-based stateful firewall enforces policy on a per data flow basis allowing the Aerohive device to manage traffic via a combination of user identity and very granular mobile device type. A user can now be granted secure access to corporate resources based on both who they are and on the type of device that they are using, providing an invaluable additional level of security regardless of the users’ location.

Wired/Wireless Access and Control

The BR100 includes 5 Ethernet switch ports, a single 802.11 b/g/n radio, a USB port for 3G/4G WAN backup, and a power adaptor. Since HiveManager manages the device’s identity, the security and network access policy is the same regardless of whether the clients are connecting via wireless or wired ports.

Cloud Proxy

Cloud-based security services ensure that branch office communications are “clean” without requiring that IT run additional security appliances at every branch office or configure web proxy information on every end user’s device. Since most of the traffic generated at branch or remote locations is destined for the Internet, Aerohive’s patent-pending Cloud Proxy automatically diverts that traffic through a cloud-based web security service, vastly reducing bandwidth costs by eliminating the need to route branch, remote office or mobile-user traffic back to a central location for filtering.

Access That Grows With Your Business

As businesses grow so do the number of branches. The BR100 runs the same HiveOS that runs on all our products, which means that as your branches grow the BR100 can leverage Aerohive’s Cooperative Control Architecture and mesh functionality to add wireless coverage to the branch locations as well. Simply install an additional HiveAP access point and the BR100 will form a wireless mesh connection with it. Within minutes your new access point will download your security policies and your secure wireless coverage will be expanded. For more, visit www.aerohive.com/products.

Warranty and Support

Every Aerohive Networks device is backed by a limited lifetime hardware warranty. Extended product and technical support may be purchased separately and can include next day advanced replacement, 24x7 or 8x5 technical support, web and email support access, and software updates. For complete support terms go to www.aerohive.com/support.

Contact us today to learn how your organization can benefit from Aerohive networking solutions.



Aerohive Networks, Inc.

330 Gibraltar Drive
Sunnyvale, California 94089 USA
phone 408.510.6100
toll-free 866.918.9918
fax 408.510.6199

www.aerohive.com

Product Specifications

Mounting

- Desktop
- Keyhole Wall Mounts

Wi-Fi

- 1x1 Single Band 802.11b/g/n

Data Rates

- 802.11b: 1,2,5,5 and 11Mbps
- 802.11g: 6,9,12,18,24,36,48, and 54 Mbps
- 802.11n (HT20/HT40): MCS0 -MCS7

Frequency Band

- 2412MHz - 2472MHz Frequency Band

Modulation

- BPSK, QPSK, 16QAM, 64QAM, DQPSK and CCK

Encryption

- WEP, AES and TKIP

Antennas

- 2x embedded antenna with diversity function

Interfaces

- 1x IEEE 802.3 (10BASE-T) and IEEE 802.3u(100BASE-TX) Compliant 10/100 Mbps RJ45 Fast Ethernet WAN Port
- 4x IEEE 802.3(10Base-T) and IEEE802.3u(100BASE-TX) Compliant 10/100Mbps RJ45 LAN Ports with auto-sensing and auto-MDI/MDI-X. IEEE 802.3x PAUSE frame flow control in full duplex
- 1x Type-A USB2.0 port backward compatible with USB1.1
- 1x Reset button to reset (on press) and load factory default settings (when pressed for more than 5 seconds)

3G Backhaul

- Verizon Pantech
- AT&T Shockwave

LEDs

- Power/Status
- WAN Port
- LAN Ports (1-4)

Physical

- 134 x 109 x 30 mm

Security

- 1 Kensington Lock Connector

Environmental

- Operating: 0 to +40°C, Storage: -20 to +70°C
- Humidity: 5 to 95% RH (non-condensing)

MTBF

- >200,000 hours based on Telecordia SR-332, Issue 2 at +25°C ambient temperature

Power

- DC 12V/1A Input

Rate	TX Power (dBm)	RX Sensitivity
Legacy Mode		
1 Mbps	18	-95
11 Mbps	18	-88
6 Mbps	18	-93
54 Mbps	18	-76
HT20 Mode		
MCS0	18	-92
MCS7	15	-72
HT40 Mode		
MCS0		-88
MCS7		-69

Features & Benefits

Flexible Hardware Platform

- Single 802.11b/g/n radio
- Automatic or dedicated mesh backup

Security

- Wireless privacy & authentication Wi-Fi CERTIFIED™ WPA™ and WPA2™, 802.11i, WEP, 802.1x, PSK
- Granular user profile-based management defines QoS, mobility policies, and security policies for each user that enters the network
- Encryption: AES:CCMP, TKIP, and RC4 (WEP only)
- Marking and policing-WMM™ (802.11e) for wireless, 802.1p and/or DiffServ
- Wi-Fi CERTIFIED WMM
- WMM power save (U-APSD)

Capacities

Firewall/VPN	5-10 Mbps
Tunnels	2 IPsec Tunnels
vLAN Support	Up to 16 VLANs (1-4094)
SSIDs	8
Clients	32
Roaming Cache	64
BSSIDs	8
User Profiles	16
TX/RX Descriptors	128
Cloud-Managed	Yes
Controller-less	Yes

SKU	Description
Aerohive Branch Router	
AH-BR-100-N-FCC	BR100, 4xFE, 1xWAN, 1 radio 802.11b/g/n, FCC regulatory domain, with power supply
AH-BR-100-N-W	BR100, 4xFE, 1xWAN, 1 radio 802.11b/g/n, configurable regulatory domain, with power supply
AH-BR-100-N-FCC-20PK	Quantity 20: BR100, 4xFE, 1xWAN, 1 radio 802.11b/g/n, FCC regulatory domain, with power supply
AH-BR-100-N-W-20PK	Quantity 20: BR100, 4xFE, 1xWAN, 1 radio 802.11b/g/n, configurable regulatory domain, with power supply
BR Accessories	
AH-ACC-PWR-12W-US	12W power supply and US power plug for BR100
AH-ACC-PWR-12W-EU	12W power supply and EU power plug for BR100
AH-ACC-PWR-12W-UK	12W power supply and UK power plug for BR100
AH-ACC-PWR-12W-AU	12W power supply and AU power plug for BR100